



**WACKER
NEUSON**
all it takes!

ARFU26

Compaction of in-situ concrete



Quality exposed concrete surface to satisfy high expectations. ARFU26

First-class compacted concrete is essential for the production of concrete surfaces. Thanks to its high-quality construction, Wacker Neuson's external vibrator ARFU26 with integrated frequency inverter offers this precision compaction. The result: Beautifully smooth and level concrete surfaces on walls, pillars and columns.

- Extremely versatile thanks to its integrated frequency inverter
- Can be connected directly to single-phase electric current.
- Long durability thanks to its powerful electric motor with stable speeds
- Available for all standard voltages and frequencies
- Fast assembly thanks to easy to use fastening clamps



ARFU26 Technical specifications

	ARFU26/6/230	ARFU26/6/115 UK
Vibrations rpm	6,000	6,000
Standard centrifugal force kN	2.3	2.3
Centrifugal force max. kN	3.47	3.47
Voltage V	220-240	110-130
Rated current A	6	12
Engine performance kW	1.1	1.1
Power cable m	2	2
Weight kg	17.98	17.98
L x W x H mm	223 x 190 x 102	223 x 190 x 102
Cable length m	15	15
Fastening	90 x 125 mm	90 x 125

Please note

that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions.

Subject to alterations and errors excepted. Applicable also to illustrations.

Copyright © 2019 Wacker Neuson SE.