



300 cfm at 200 psig—
8.5 m³/min at 14 bar

Available in T2 T3 AF



375 cfm at 100 psig—
10.6 m³/min at 7 bar

100% **T2** **T3** **AF**



375 cfm at 150 psig—
10.6 m³/min at 10 bar

Available on  Taylor & Francis Group

- Easy and inexpensive to replace if damaged
- Easily removed as one assembly for major service
- Exposed, single point lifting bail

- Large side doors provide access to engine, oil filters, compressor and tool compartment
- Rear service panel provides access to rear of machine
- Serviceable components within easy reach
- Routine maintenance is simplified
- Reduced downtime and service cost
- Service doors feature non-rusting hinges and stainless steel T-type door retainers

- 3" x 5" square drawbar
- Adjustable height hitch
- Quick-change hitch
- Screw jack with pad
- Transport security chains
- E-Z lube axle lubrication
- Heavy duty leaf spring suspension
- Tail lights

- Hinged, padlockable cover
- Mechanical air pressure gauge, hour meter, ignition start switch

- Idle warm-up valve
- Optional gauges available
- High/Low pressure selector valve allows dual pressure capability without making mechanical adjustment (available on high pressure models only)

- Pneumatic inlet valve and unloaded starting

- High engine temperature, low engine oil pressure, high compressor discharge temperature, low engine speed and low fuel level

- Separate filters for engine and compressor

- All-weather, all-climate fluid

- 1 year standard warranty
- 2 year standard air end warranty

- 5 year or 10,000 hour air end warranty when continuously serviced at the recommended intervals with Sullair AWF compressor fluid and filters
- Diesel engine warranty applies - contact Sullair for more information

- Meets US EPA sound requirements of 76 dBA @ 7 meters

AF See pg 57 for additional information on
used or Aftercooled & Filtered models available

[illegible]